


Benzene Specific C_6H_6 No. H-10-101-10



	Extended Range	Standard Range	Extended Range
Range (ppmv)	2.5 - 20	5 - 40	25 - 200
No. of Pump Strokes	10	5	1
Sample Volume (mL)	1000	500	100
Sample Time (min)	10 x 3	5 x 3	3
Correction Factor	0.5	1	5

Precision (Relative Standard Deviation)*: $\leq \pm 12\%$


Humidity: No effect 5 - 100% RH

Temperature Range: No effect 0 - 40°C (32 - 104°F)

Storage Life: 1 year in darkness at 5 - 25°C (40 - 77°F). Refrigeration preferred.

Color Change: White → Light Brown

Reaction Principle: Pretube removes interferences



<u>Cross-sensitivity:</u> Substance	Concentration (ppmv)	Apparent Reading*
Isobutylene	100	~2 (faint)
n-Hexane	10	0
n-Octane	100	0
Toluene	35	0#
m-Xylene	50	0#
β-Pinene	50	~2 (very faint)
CO	10	7
H ₂ S	25	0

* Data based on Honeywell pumps and tubes used in standard range.

#With 10 strokes, toluene and xylene at 50 ppm read 2 ppm and 100 ppm octane reads ≤ 2 ppm.

Other Data: Without the pretube the readings are 30% higher.