Mercaptans RSH

No. H-10-129-20



	Extended Range	Standard Range	Extended Range
Range (ppmv)	2.5 - 60	5 - 120	10 - 240
No. of Pump Strokes	2	1	0.5
Sample Volume (mL)	200	100	50
Sample Time (min)	2 x 2.0	2.0	1.0
Correction Factor	0.5	1	2.1

<u>Precision (Relative Standard Deviation)*</u>: ≤±20%

<u>Linearity with No. of Pump Strokes</u>: $r^2 = 0.999$

Humidity: No effect between 5 - 90% RH.

Temperature Range: No effect between 0 - 40°C (32 - 104°F)

Storage Life: 1 year in darkness at 5 - 25°C (40 - 77°F). Refrigeration preferred.

 $\underline{\text{Color Change}} \colon \text{White} \ \to \ \text{Yellow}$

 $\underline{\text{Reaction Principle}} : \quad 2\text{RSH + PdSO}_4 \ \rightarrow \ (\text{RS})_2\text{Pd + H}_2\text{SO}_4$

Cross-sensitivity: Substance	Concentration (ppmv)	Apparent Reading*	Corr. Factor
H ₂ S	500	O ¹	-
CO	500	O ²	-
Diethyl sulfide	5000	30³	-
Ethyl mercaptan	60	60	1.0
Propyl mercaptan	60	60	1.0
Butyl mercaptan	60	29	2.0
Acetylene	2000	O ⁴	-
Ethylene	2000	O ⁵	-

^{*} Data based on Honeywell pumps and tubes used in standard range.

¹ Up to 500 ppm H₂S is trapped in the pretreatment layer.

² Gray through the entire tube, will not affect RSH reading in mixtures.

³ Interferes in mixtures; may result in high response.

⁴ Pale brown through the entire tube, will not affect RSH reading in mixtures.

⁵ Light peach through the entire tube, will not affect RSH reading in mixtures.