

# Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

## Acrolien

C (TLV): 0.1 ppm

## CH<sub>2</sub>:CHCHO

STEL (TLV): NA

## SAE - 4

Flammable Range: 2.8 – 31%

### Specification:

	Extended	Standard	Extended
Measurement Range		10 – 800 ppm	
No. of Pump Strokes		2 (200 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	2.0 minutes per pump stroke (100 mL)		
Color Change	Yellow → Pink		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F) in Refrigerator		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	3CH <sub>2</sub> :CHCHO + (NH <sub>2</sub> OH) <sub>3</sub> H <sub>3</sub> PO <sub>4</sub> → H <sub>3</sub> PO <sub>4</sub> H <sub>3</sub> PO <sub>4</sub> + Base → Phosphate		
Relative standard deviation	± 10 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

### Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Aldehydes		+	Yellow to Pink
Ketones		+	Yellow to Pink
H <sub>2</sub> S		+	Yellow to Light Pink

### Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



**Manufactured By:** Uniphos Envirotronic Pvt. Ltd.  
Nahuli (PO), Umbergaon (Tal.)  
Valsad (Dist), Gujarat, India – 396108

Rev.0812