

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Trichloroethylene $\text{Cl}_2\text{C}:\text{CHCl}$ SCE-4L

TWA (TLV): 50 ppm

STEL (TLV): 100 ppm

Flammable Range: NA

Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	20 – 250 ppm	Do not extend
No. of Pump Strokes	2 (200 mL)		
Volume Correction Factor (VCF)*	1.0		
Sampling Time	1.5 minutes per pump stroke (100 mL)		
Color Change	White → Yellow		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	$\text{Cl}_2\text{C}:\text{CHCl} + \text{Cr}^{6+} + \text{H}_2\text{SO}_4 \rightarrow \text{Cl}_2$ $\text{Cl}_2 + \text{o-Tolidine} \rightarrow \text{Reaction product}$		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
1,2 Dichloroethylene		+	White to Yellow
Cl_2		+	White to Yellow

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0812