

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Furfural

C₅H₄O₂

SFL-2M

TWA (TLV): 2 ppm

STEL (TLV): NA

Flammable Range: 2.1 – 19.3 %

Specification:

	Extended	Standard	Extended
Measurement Range	Do not extend	1 - 16 ppm	Do not extend
No. of Pump Strokes		4 (400 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	2 minutes per pump stroke (100 mL)		
Color Change	Pale Yellow → Orange		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	C ₅ H ₄ O ₂ + 2,4-Dinitrophenylhydrazine → Dinitrophenylhydrazone		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Tube Reading (ppm)	Colour change / Comments
Ketones		+	Pale Yellow to Orange

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0812