

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Hydrogen Chloride HCl

SHC- 2M

TWA (TLV): NA

Ceiling (TLV): 2 ppm

Non Flammable

Specification:

	Extended	Standard	Extended
Measurement Range	1 – 10 ppm	2 – 20 ppm	4 – 40 ppm
No. of Pump Strokes	4 (400 mL)	2 (200 mL)	1 (100 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	1 minute per pump stroke (100 mL)		
Color Change	Yellow → Pink		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F).		
Reaction Principle	HCl + Base → Reaction product		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
HF		+	Yellow → Pink
NH ₃	100	No	No effect
NO ₂	200	No	No effect
H ₂ S	800	No	No effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0812