

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Isopropyl alcohol C_3H_7OH

SIP-7M

TWA (TLV): 400 ppm

STEL (TLV): NA

Flammable Range: 2 – 12.7 %

Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	0.1 – 2.5 %	Do not extend
No. of Pump Strokes	3(300 mL)		
Volume Correction Factor (VCF)*	1.0		
Sampling Time	1.5 minutes per pump stroke (100 mL)		
Color Change	Orange → Brownish green with brown top		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	$C_3H_7OH + Cr^{6+} + H_2SO_4 \rightarrow Cr^{3+}$		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Alcohols		+	Orange to Brownish green
Esters		+	Orange to Brownish green
Ketones		+	Orange to Brownish green
Aromatic Hydrocarbons		+	Orange to Brownish green
H ₂ S		+	Orange to Brownish green
CO	15000	No	No Effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0812