



## Calibration Gas Source





Chlorine (Cl <sub>2</sub> )	0.5 - 25 PPM 0.5 - 25 PPM 0.5 - 25 PPM
Air Flow Rate.  Replacement Cell Life	

The The lectrochemical generating cell is interchangeable and provides multiple gas and concentration options quickly, safely and easily. By simply inserting the appropriate cell in the instrument, the user is ready to calibrate.

The The 101's compact size and light weight provide for a safe and easy calibration even for the least accessible detection points. The two "AA" batteries powering the instrument combined with an efficient design provide the user with a light-weight instrument weighing approximately 1 pound or 0.5 Kg.

The FIL 101 will be sold as a kit including a *free* generation cell (specify gas and concentration), two "AA" batteries, a delivery hose, and an instruction manual.

The FL 101 gas generator's features include:

- Non-Hazardous shipping
- Designed to meet intrinsic safety requirements
- Compact "hand-held" design
- Interchangeable calibration gases and concentration
- Low power consumption
- Lowest cost calibration
- Alkaline battery powered

Advanced Calibration Designs, Inc. • 2024 W. McMillan Street • Tucson, Arizona 85705 • U.S.A.

Telephone: (520) 290-2855 ● Fax: (520) 290-2860 ● E-Mail: ACD@goacd.com ● www.GoACD.com