



SPECIFICATIONS

Product Description: **PANEL, AIR FILTRATION**
Part Number: **9872, 9872 W/O**
Style: **PORTABLE, 2 WORKER SYSTEM**

GENERAL DESCRIPTION:

Allegro air filtration panels filter impurities and hydrocarbons from an air compressor to convert to breathable air. To meet OSHA requirements an optional CO monitor is available for continuous monitoring of carbon monoxide levels. Panel provides up to 30 CFM of air within a 5-125 PSI range.

CONSTRUCTION:

- Housed in a portable, rugged Pelican case with carrying handle, latches for protection and security
- A 16 gauge powder coated steel stand, for support
- All brass plumbing with quick-disconnect Hansen couplers



CO MONITOR:

Power source: 115V AC to 9V DC power adapter for continuous power supply
9V DC Alkaline battery (primary or as back-up for AC adapter)

Alarm Setting: 10 PPM (Canada: 5PPM)

Ext. Connections: Optional Remote Strobe Alarm

Audible: 90 decibel Piezo Alarm

Visual: External power LED light signal

Sensor: Electrochemical, replaceable

Display: Liquid crystal

Keys: Mode & Set

Modes: Normal operation, peak, battery charge and calibration mode

Calibration: Self adjusting calibration to 20 PPM CO

FILTRATION SYSTEM:

First Stage: 5 micron particulate filter element and automatic mechanical drain

Second Stage: 0.010 micron coalescing filter element and manual drain

Third Stage: 0.003 micron activated carbon filter element and manual drain

Regulator: High pressure, adjusting pressure knob, 0-160 pressure gauge and external relief valve

Flow Meter: Adjustable metering valve, range from 0.0-1.0 LPM

DIMENSIONS:

Length	Width	Height	Weight
13"	6"	12"	14 lbs.