

Closed-circuit breathing apparatus Dräger PSS® BG 4 plus

Specially designed for demanding tasks: The Dräger PSS BG4 plus closed-circuit breathing apparatus combines uncompromising safety with outstanding respiratory protection and wearer comfort. Innovative in design, it provides the wearer with up to four hours of breathing air in toxic environments.



- BREATHING AIR FOR UP TO 4 HOURS
- HIGHEST BREATHING COMFORT WITH AN INTEGRATED COOLING SYSTEM
- ERGONOMICALLY SHAPED CARRYING PLATE
- REDUCED EXPOSURE FROM A WELL BALANCED SYSTEM
- IMPROVED HARNESS AND INTELLIGENT BREATHING HOSE ROUTING FOR EXCELLENT FREEDOM OF MOVEMENT
- NEW DRÄGER FPS 7000 RP FULL FACE MASK WITH INTEGRATED DRINKING VALVE



Whenever emergency teams are saving lives or extinguishing fires, above or below the ground, the Dräger PSS BG 4 plus comes into its own. Whether used during rescue or fire fighting missions in mines, tunnels or underground train ducts, or in assignments with long access routes, the closed-circuit breathing apparatus is the first choice. More than 25,000 professional users rely on the Dräger PSS BG 4 worldwide.

OPTIMIZED IN CONJUNCTION WITH OUR CUSTOMERS

Our products must meet the precise needs of the user and, for this reason, we involve our customers in the development process. Modifications to the proven Dräger PSS BG 4 are the result of practical experience and constant monitoring to ensure the highest quality standards. We listened to our customers and implemented their

requirements in the new Dräger PSS BG 4 plus. Numerous improvements and new accessories have increased safety and durability and further improved the ease of servicing. The modifications are available individually or a practical retrofit set upon request.

EXCELLENT SUITABILITY FOR EXTENDED USE

The slight positive pressure breathing circuit protects the wearer by preventing hazardous substances from entering the sealed breathing system. Depending on the application, the duration of use is up to four hours. A CO₂ absorber removes carbon dioxide from the exhaled air. At the same time the breathing air is enriched with oxygen from the oxygen cylinder. Before the regenerated breathing air is inhaled again it flows through the breathing air cooler.





Dräger PSS® BG 4 plus Highest safety in extreme situations

PRODUCT ENHANCEMENTS

Both the minimum valve, which enriches the breathing air with additional oxygen upon demand, and its attachment clip have been treated with a special coating to protect against corrosion. A redesigned clip simplifies the fitting of the valve. The area around the pressure reducer has been reinforced and additional reinforcement protects the carrying plate, providing greater stability when handling the unit complete with oxygen cylinder. To reduce the temperature of the inhaled air and minimise physical stress to the wearer, the breathing air cooler can be filled with ice.

PRACTICE-ORIENTED INNOVATIONS

Newly developed heat protection for the breathing hose and housing are also optionally available to further reduce the temperature of the inhaled air. A T-piece with water trap can be retrofitted to the facemask to prevent water from collecting in the flow area of the device. Any liquid discharged into the breathing circuit from the drain valve is optionally collected in a super absorbent fleece. The fleece is designed for single use and is easily disposed.

SIMPLE CO, DISPOSAL

Complete with integral dust filter, the flow-sensitive CO₂ absorber is available as either a single-use absorber or refillable cartridge. Fitted with a newly designed spring clip, the CO₂ absorber offers increased spring durability. The position and size of the breathing hose connectors

have also been optimized for easier handling during assembly. For hygienic storage the single-use absorbers are available in a sealed bag.

PROVEN WEARER COMFORT

The ergonomically shaped carrying plate, the low weight and the proven harness with adjustable shoulder straps and easy to use "pull-forward" design provide more freedom of movement with less effort. The practical breathing hose routing across the shoulders ensures optimum balance on the wearer's back.

PERFECT RESPIRATORY PROTECTION MONITORING

The data captured by the Dräger Sentinel II electronic monitoring unit can be transmitted to Dräger PSS Merlin telemetry boards. This electronic monitoring and communications system displays Sentinel II data for each of the wearers who are logged on. As a result, entry control personnel are able to view the current status of each of the device wearers and can respond immediately to an emergency.

DRÄGER PSS® BG 4 PLUS - THOUGHT THROUGH TO THE MINUTEST DETAIL



TECHNICAL DATA

Dräger PSS® BG 4 plus		
Duration of use	4 h according to EN 145 and NIOSH	
Weight, ready for use (kg/pound)	15,5 kg / 34.17 pound (incl. mask, full oxygen cylinder (aluminum), CO_2 absorber and approx. 1,2 kg / 2.65 pound cooling ice)	
Dimensions (H x W x D) (mm/inch)	595 x 450 x 185 mm / 23.43 x 17.72 x 7.28 inches	
Constant oxygen metering (I/min O ₂)	1.5 to 1.9	
Minimum valve (I/min O ₂)	> 80	
Breathing bag volume (I)	5,5	
Bypass valve (I/min)	> 50	
Operating temperatures	-40°C / -40°F to +90°C / +194°F (if stored at room temperature)	
Approvals	EN 145, Ex protection according to EN 50020, Eex IIC T4, Eex ial and NIOSH	

ACCESSORIES

FULL-FACE MASKS | ABSORBERS | OXYGEN CYLINDERS

Required for operation



Dräger FPS 7000 RP Excellent fit, extremely large field of view, optional drinking connection R 56 326



Dräger Panorama Nova EPDM PC RP Safe, comfortable fullface mask in various designs, mask body from EPDM R 53 306



Dräger CO₂ absorber single-use cartridge, grey R 34 360



Dräger CO₂ absorber refillable cartridge, transparent R 34 367



Dräger CO₂ absorber refillable cartridge, arev R 34 277

Accessories for optimized protection



T-piece with water trap Prevents the collection of water in the flow area of the device connection R 34 725



Heat protection for breathing hoses and housing, reduces the temperature of the inhaled air when fire fighting R 34 644



Ice cooler To the insertion of an ice plug R 34 710



Drägersorb® 400 Absorption Agent, in pellet form, for the refillable cartridge

18 kg/ 39 lb canister 67 37 985



Dust sieve Sieving the soda lime before pouring into the refillable cartridge R 32 618



Dust filter (50 off) 4058167



Filling station R 33 752

EXPANSION SETS

Freezer canister cooler Dräger PSS® BG 4 To produce ice plugs





Retrofit kit Step 1 for NIOSH R 34 681



Test instrument Dräger Test-it 6100 For Dräger PSS BG 4 & BG 174

Isolation for

under -15°C 4056725





Test kit

testing

R 33 777

required for

With all adapters

Antifog Spray Prevent fogging Dräger PSS® BG 4 For operations of visor with temperatures R 21120



Dräger PSS® BG 4 Harness Optimized, highly flexible strap routing for a comfortable fit



Merlin Radio Kit Europe 33 54 430 Merlin Radio Kit US



Easy retrofit for increased safety and comfort

Dräger PSS® BG 4 Vibration protection Ensures safe transportation R 34 238



Mount For the hinge of the cover plate R 34 642



Improved Hose Routing R 34 630



33 56 185



Single Use Absorber To catch fluid out of drain valve R 34 633



Expansion set Dräger Bodyguard II high pressure R 34 259









Dräger PSS® BG 4 plus Optional: Heat protection against radiation heat



Dräger FPS 7000 RPOptimized field of view, absolutely tight fit

ALL FUNCTIONS UPON A GLANCE

The Dräger PSS BG 4 plus is equipped with the Dräger Bodygard II fully electronic signal and warning unit. Controlled via large pushbuttons, it combines a multitude of functions. During use it quickly provides the wearer with important information, thereby reducing the risk potential. Using battery warning thresholds the Dräger Bodygard II reliably indicates current operational status.

Monitoring functions:

- Cylinder pressure (analog and digital)
- Remaining duration of use (time remaining until residual pressure warning)
- Temperature indication upon the press of a button
- Automatic recording of all mission data

Optical and acoustic warning signals:

- Residual pressure warning
- Two additional selectable electronic alarm thresholds
- Automatic alarm for lack of movement
- Manual emergency call alarm

HIGH PERFORMANCE SODA LIME

Drägersorb 400 has been specially designed for the absorption of CO₂ in closed-circuit breathing apparatus which significantly contributes to long-term performance capabilities, especially

under the likely conditions of use for the Dräger PSS BG 4 plus. Drägersorb 400 i s characterized by a very high abrasion resistance.

EASY MAINTENANCE

Both the retrofittable vibration protection and the robustly designed locking hinge increase the safety of the Dräger PSS BG 4 plus during transportation. For maximum operational readiness, the Dräger PSS BG 4 plus has been designed to allow the fast assembly and/or removal of device components without special tools.

NEW IN THE TEAM: THE FULL-FACE MASK DRÄGER FPS 7000 RP

The full-face mask Dräger FPS 7000 complements the ideally Dräger Panorama Nova product family. With an improved head harness and available in various sizes, it adjusts perfectly to every face shape. With its dual sealing line, the almost natural field of view and easy-tooperate wiper, guarantees a safe tight fit and good all-round visibility. An optional adapter enables the connection of the comfortable CamelBak* drinking system. Liquid only flows through the straw when the integrated biting valve is pressed together by the teeth.

^{*}CamelBak® is a trademark of Camelbak Products, LLC.

ORDER INFORMATION

Dräger PSS® BG 4 plus		
Dräger PSS® BG plus CP	High pressure, Canada	4057243
Dräger PSS® BG plus AP	High pressure, NIOSH	4057227
	Further variants can be found in the price list or are available on request.	-
Required for operation		
Dräger FPS 7000	Full face mask with central connecting for closed circuit breathing apparatus Dräger PSS BG 4 plus.	R 56 326
RP-EPDM-M2-PCas-CR	Mask body, inner mask and head harness made of EPDM.	
	With anti-scratch coated polycarbonate visor and wiper.	
	Available as an option is the CamelBak drinking system	
Dräger Panorama Nova EPDM RP PC	Full face mask with plug-in connection, polycarbonate visor and wiper	R 53 306
	for closed circuit breathing apparatus. Approved for mining and fire departments,	
	tested for EN 136 with CE mark	
	Further variants and sizes on request	
Accessories for communication		
Receiver with ear cup and	Optionally, the Dräger FPS 7000 RP can be equipped with a telephone device or a Dräger MS-COM.	R 28 495
microphone	Both telephone device and Dräger FPS 7000 MS-COM are approved in accordance to 94/9/EG	
	for operations in explosive areas	<u> </u>
Expansion sets		
Dräger PSS® BG 4 sticker	Large, front left	R 34 682
for cover	Large, front right	R 34 683
	Small, front left	R 34 684
	Small, front right	R 34 685
Upgrade Kit low warning	To convert Dräger BG 4 and Dräger PSS BG 4 high pressure devices on new control wire	R 34 630
Upgrade kit	Mod. 1 (EN)	R 34 641
Radio Kit for Dräger PSS® BG 4 plus		
Dräger Bodyguard IR-Link software	-	33 51 342
Dräger Merlin/Bodyguard		33 54 304
0 ,0		00 0 1 00 4
datalog cable		

HEADQUARTERS:

Dräger Safety AG & Co. KGaA Revalstrasse 1 23560 Lübeck, Germany

www.draeger.com

SUBSIDIARIES:

AUSTRALIA

Draeger Safety Pacific Pty. Ltd. Axxess Corporate Park Unit 99, 45 Gilby Road Mt. Waverley. Vic 3149 Tel +61 3 92 65 50 00 Fax +61 3 92 65 50 95

CANADA

Draeger Canada Ltd. 7555 Danbro Crescent Mississauga, Ontario L5N 6P9 Tel +1 905 821 8988 Fax +1 905 821 2565

P. R. CHINA

Beijing Fortune Draeger Safety Equipment Co., Ltd. A22 Yu An Rd, B Area, Tianzhu Airport Industrial Zone, Shunyi District, Beijing 101300 Tel +86 10 80 49 80 00 Fax +86 10 80 49 80 05

FRANCE

Dräger Safety France SAS 3c route de la Fédération, BP 80141 67025 Strasbourg Cedex 1 Tel +33 3 88 40 59 29 Fax +33 3 88 40 76 67

MEXICO

Draeger Safety S.A. de C.V. Carretera San Luis Potoski Km 21
Bodega No. 1 y 2
Condominio Industrial
"Poligono Empresarial Santa Rosa Bloque SMED"
Querétaro, Qro
México, C.P. 72220
Tel +52 442 246-1113
Fax +52 442 246-1114

NETHERLANDS

Dräger Safety Nederland B.V. Edisonstraat 53 2700 AH Zoetermeer Tel +31 79 344 46 66 Fax +31 79 344 47 90

REP. OF SOUTH AFRICA

Dräger South Africa (Pty) Ltd. P.O.Box 68601 Bryanston 2021 Tel +27 11 465 99 59 Fax +27 11 465 69 53

SINGAPORE

Draeger Safety Asia Pte Ltd 67 Ayer Rajah Crescent #06-03 Singapore 139950 Tel +65 68 72 92 88 Fax +65 65 12 19 08

SPAIN

Draeger Safety Hispania S.A. Calle Xaudaró 5 28034 Madrid Tel +34 91 728 34 00 Fax +34 91 729 48 99

UNITED KINGDOM

Draeger Safety UK Ltd.
Blyth Riverside Business Park
Blyth, Northumberland
NE24 4RG
Tel +44 1670 352 891
Fax +44 1670 356 266

Draeger Safety, Inc. 101 Technology Drive Pittsburgh, PA 15275 Tel +1 412 787 8383 Fax +1 412 787 2207

Distribtued by
AFC International Inc
PO Box 894
DeMotte IN 46310
800.952.3293 • 219.987.6825

fax 219.987.6826 • sales@afcintl.com • www.afcintl.com