

WARRANTY EXCLUSIONS AND LIMITATION OF LIABILITY

IF THE USER DOES NOT ACCEPT THE FOLLOWING TERMS, THE USER SHOULD NOT USE THE SAFEAIR BADGES AND COLOR COMPARATORS.

Seller warrants that, for the lesser of one (1) year or the shelf-life provided on the Seller's product, its packaging or its literature, its products shall conform to the description of such products as provided on the Seller's product, its packaging or its literature. THIS WARRANTY IS EXCLUSIVE, AND SELLER MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Seller's warranties made in connection with this sale shall not be effective if Seller has determined, in its sole discretion, that Buyer has misused the products in any manner, has failed to use the products in accordance with safe industry standards and practices, or has failed to use the products in accordance with Seller's written operating instructions, or other instructions furnished by Seller to Buyer.

Seller's sole and exclusive liability and Buyer's exclusive remedy with respect to products to Seller's satisfaction to be defective or nonconforming shall be replacement of such products without charge or refund of the purchase price, in Seller's sole discretion, upon the return of such products in accordance with Seller's instructions. All claims must be brought within one (1) year of shipment, regardless of their nature.

SELLER SHALL NOT IN ANY EVENT BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES OF ANY KIND RESULTING FROM ANY USE OR FAILURE OF THE PRODUCTS, EVEN IF SELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE INCLUDING, WITHOUT LIMITATION, LIABILITY FOR LOSS OF USE, LOSS OF WORK IN PROGRESS, DOWN TIME, LOSS OF REVENUE OR PROFITS, FAILURE TO REALIZE SAVINGS, LOSS OF PRODUCTS OF BUYER OR OTHER USE OF ANY LIABILITY OF BUYER TO A THIRD PARTY ON ACCOUNT OF SUCH LOSS, OR FOR ANY LABOR OR ANY OTHER EXPENSE, DAMAGE OR LOSS OCCASIONED BY SUCH PRODUCT INCLUDING PERSONAL INJURY OR PROPERTY DAMAGE UNLESS SUCH PERSONAL INJURY OR PROPERTY DAMAGE IS CAUSED BY SELLER'S GROSS NEGLIGENCE.

Warning: Keep out of reach of children, if ingested seek medical attention immediately.



2557 Production Rd.
Virginia Beach, VA 23454
Phone: (757) 431-2260 Fax: (757) 216-6209
E-mail: customerservice@morphtec.com

©1997, Morphix Technologies®
Publication Number: KM1-23A.10-0714
US Patent Number: 6,284,198



Operating Instructions for Aromatic Isocyanates Badge For the detection of Toluene Diisocyanate (TDI) and Methylene Diphenyl Diisocyanate (MDI) (Part Number: 382001)

Technical Summary

Physical Specifications:

| | |
|-------------------------|------------------------------------|
| Dimensions | (74 ± 1 mm) x (41 ± 1 mm) x (1 mm) |
| Weight | 1.5 g |
| Refrigerated shelf life | 1 year |
| Color change | off-white to red |

Sampling Parameters:

| | TDI | MDI |
|-------------------------------------|-----------------|----------------------------|
| Exposure dose: | | |
| Badge | 5 ppb-hr | 3.5 ppb-hr |
| Badge with color comparator | 5 – 140 ppb-hr | |
| Minimum detectable limit (8 hours) | 0.6 ppb | 0.4 ppb |
| Maximum recommended sampling time | 24 hours | 24 hours |
| Minimum recommended sampling time | 15 minutes | 15 minutes |
| Relative humidity range | 11% - 87% | 11% - 87% |
| Face velocity range | 10 – 100 cm/sec | 10 – 100 cm/sec |
| Temperature range | 60°F - 91°F | 60°F - 91°F |
| Light effect – UV (direct sunlight) | | not recommended above 4 hr |
| Light effect – visible | no effect | no effect |
| Color stability | two weeks | two weeks |

Applications:

The SafeAir aromatic isocyanates badge may be used for personnel or area monitoring for exposure times ranging from 15 minutes to 24 hours. For higher resolution when monitoring for TDI, the SafeAir aromatic isocyanates badge may be used in conjunction with the SafeAir TDI color comparator (part number: 383005). **For exposure times less than 30 minutes, it is recommended to allow the exposed badge to stand for at least 30 minutes before reading the exposure dose with the color comparator.**

The SafeAir aromatic isocyanates badge is designed to monitor TDI and/or MDI vapors in the air. **It is not recommended to use the badge to monitor TDI or MDI aerosols.**

Cross Interferences:

Other aromatic diisocyanates and high concentrations of hydrazines are known interferences. No other interferences are known.

Introduction

Based on the available toxicity data in animals and epidemiologic studies of humans, aromatic diisocyanates such as TDI and MDI are strong respiratory sensitizers.¹ Repeated exposures or a single large dose may cause sensitization. Chronic overexposure has also been reported to cause lung damage including fibrosis. OSHA and NIOSH exposure limit for TDI is 0.02 ppm (TWA), the OSHA exposure limit for MDI is 0.02 ppm (ceiling) and the NIOSH exposure limit for MDI is 0.005 ppm (TWA).

Aromatic diisocyanates, such as toluene diisocyanate (TDI) and methylene diphenyl diisocyanate (MDI), are commonly used to make various polymers such as polyurethanes. Polyurethanes have significant application in the manufacture of rigid and flexible foams. They are also used in the production of adhesives, elastomers and coatings. Polyurethane coatings are preferred in the automotive refinishing industry where high performance coatings are required.

¹ www.epa.gov/dfe/pubs/auto/profile/toxicology1a.pdf

Principle of Operation

The SafeAir aromatic isocyanates badge is a monitoring system designed to indicate the presence of TDI and/or MDI at concentrations below the permissible exposure limit. The SafeAir aromatic isocyanates badge detects the presence of TDI and/or MDI by forming a color change in the shape of an exclamation mark inside the triangle. This indication is produced by a color-forming reaction, which occurs when TDI and/or MDI react with a flat indicator layer.

Operating Instructions

1. Remove the pouch from the refrigerator and allow it to warm to room temperature.
2. Remove the badge from its protective pouch.
3. For personnel monitoring, attach the badge near the user's breathing zone (i.e. the collar) with the front side exposed to the surrounding atmosphere.
4. For area monitoring, attach the badge to a stand and mount in a centralized area with the front side exposed to the surrounding atmosphere.
5. The exclamation mark appears within the triangle when TDI and/or MDI are present. Please note that the exclamation mark will appear on the front of the badge.
6. To obtain the average concentration, divide the exposure dose (ppb-hr) by the exposure time in hours (hr).

Storage

The SafeAir aromatic isocyanates badge should be refrigerated in its sealed bag at all times.

Benefits

1. Accurate Detection: The SafeAir aromatic isocyanates badge is designed to react selectively with TDI and/or MDI with minimum interference from other substances.
2. Applications: The SafeAir badge may be used for personnel screening and for area monitoring or area mapping.
3. Ease of Use: The SafeAir badge is a direct-read device that gives immediate, on-site results.

Other Available Monitors

1. SafeAir Badges:

| | | |
|---------------------------|-------------------|----------------|
| Ammonia | Hydrazine | Phosgene |
| Carbon Monoxide | Hydrogen Chloride | Phosgene Dura |
| Chlorine | Hydrogen Sulfide | Phosgene Medi |
| Chlorine/Chlorine Dioxide | Mercury | Sulfur Dioxide |
| Formaldehyde | Ozone | |
2. SafeAir Color Comparators:

| | | |
|-----------------------------|---------------------|---------------|
| Chlorine | Hydrogen Chloride | Phosgene Dura |
| Chloroformates ¹ | Phosgene | Phosgene Medi |
| Hydrazine | Phosgene ext. range | |

If you require SafeAir monitors for a chemical hazard not listed, please contact Morphix Technologies® for a free compound consultation at (800) 808-2234.

¹ To be used with the SafeAir phosgene badges