



RAE Systems, Inc.
1339 Moffett Park Dr.
Sunnyvale, CA 94089 USA

Telephone 408-752-0723
Tube Orders 1-888-723-8823
Web www.raesystems.com

Gas Detection Tube Data Sheet

Hydrogen Sulfide H₂S No. 10-103-15

	Extended Range	Standard Range	Extended Range
Range (ppmv)	5 - 60	10 - 120	20 - 240
No. of Pump Strokes	2	1	0.5
Sample Volume (mL)	200	100	50
Sample Time (min)	2 x 1.5	1.5	1
Correction Factor	0.5	1	2

Precision (Relative Standard Deviation)*: $\leq \pm 12\%$

Linearity with No. of Pump Strokes: $r^2 = 0.999$

Humidity: No effect 5 - 85% RH

Temperature Range: 0 - 40°C
(32 - 104°F)

Temp (°C/°F)	0/32	10/50	24/75	40/104
Corr. Factor	0.88	0.96	1.0	1.1

Storage Life: 2 years in darkness at 5 - 25°C (40 - 77°F). Refrigeration preferred.

Color Change: White → Brown

Reaction Principle: $H_2S + Pb(OAc)_2 \rightarrow PbS + 2HOAc$

<u>Cross-sensitivity:</u> Substance	Concentration (ppmv)	Apparent Reading*
CO	250	0
CH ₄	25000	0
NH ₃	100	0
NO ₂	200	0 [†]
CS ₂	100	0
Methyl mercaptan	1000	0 [#]
Diethyl sulfide	100	0
Isobutylene	100	0
Toluene	100	0

*Data based on RAE pumps and tubes used in standard range.

[†] Interferes in mixtures; may result in transient light brown H₂S response.

[#] No effect in mixtures. Concentrations in the high % range leave a yellow color over the entire tube.

Caution: Dispose of spent or expired tubes according to local regulations.

Possibly hazardous materials are given under the section Reaction Principle.